

GOODWE

ET LV Series

5-20kW | Three phase | 2/3/4 MPPTs
Hybrid inverter

The GoodWe ET LV Series inverter (5-20kW) is ideal for residential PV systems, offering seamless integration with low-voltage (48V) batteries. Designed for flexibility, it supports a wide range of battery capacities and brands, including GoodWe's own Lynx A G3, Lynx U G3, and BAT 14kWh low-voltage batteries-making it a versatile choice for homeowners seeking reliable energy storage solutions.



High Performance

- 20A per string & 200% PV oversizing
- Dual independent battery inputs with 416A



Smart Control & Monitoring

- Seamless switching < 4ms
- Generator compatibility and charge for battery



Superb Safety & Reliability

- AI-driven AFCI optional¹
- Type II SPD on both DC&AC sides
- IP66 ingress protection



Flexible & Adaptable Applications

- Unbalanced output up to 150%
- Compatible with both Li-Ion/Lead-acid batteries

1: Optional devices or functions are purchased separately.

Technical Data	GW5K-ET-L-G10	GW6K-ET-L-G10	GW8K-ET-L-G10	GW10K-ET-L-G10	GW12K-ET-L-G10	GW15K-ET-L-G10	GW20K-ET-L-G10
Battery Side							
Battery Type	LFP (LiFePO ₄) / Lead-acid						
Nominal Battery Voltage (V)	48						
Battery Voltage Range (V)	40 ~ 60						
Start-up Voltage (V)	30						
Number of Battery Inputs	1	1	1	1	1	2	2
Max. Continuous Charging Current (A)	125	135	175	220	250	165 / 165	208 / 208
Max. Continuous Discharging Current (A)	125	135	175	220	250	165 / 165	208 / 208
Max. Charging Power (kW)	5	6	8	10	12	15	20
Max. Discharging Power (kW)	5.5	6.6	8.8	11.0	13.2	16.5	22.0
PV Side							
Max. Input Power (kW)	10	12	16	20	24	30	40
Max. Input Voltage (V) ¹	1000						
MPPT Operating Voltage Range (V) ²	150 ~ 850						
Start-up Voltage (V)	180						
Nominal Input Voltage (V)	620						
Max. MPPT Current (A)	20 / 20	20 / 20	20 / 20	20 / 20 / 20	20 / 20 / 20	20 / 20 / 20 / 20	20 / 20 / 20 / 20
Max. MPPT Short Circuit Current (A)	26 / 26	26 / 26	26 / 26	26 / 26 / 26	26 / 26 / 26	26 / 26 / 26 / 26	26 / 26 / 26 / 26
Number of MPPTs	2	2	2	3	3	4	4
Number of Strings per MPPT	1 / 1	1 / 1	1 / 1	1 / 1 / 1	1 / 1 / 1	1 / 1 / 1 / 1	1 / 1 / 1 / 1
AC Side (On-grid)							
Nominal Power (kW)	5	6	8	10	12	15	20
Max. Power (kW)	5.5	6.6	8.8	11.0	13.2 ³	16.5 ³	22.0 ³
Nominal Apparent Power Output to Grid (kVA)	5	6	8	10	12	15	20
Max. Apparent Power to Utility Grid (kVA) ⁴	5.5	6.6	8.8	11.0	13.2	16.5	22.0
Nominal Apparent Power from Grid (kVA)	5	6	8	10	12	15	20
Max. Apparent Power from Grid (kVA)	48.3	48.3	48.3	48.3	48.3	48.3	48.3
Nominal Voltage (V)	400 / 380, 3L / N / PE						
Voltage Range (V)	170 ~ 290						
Nominal Frequency (Hz)	50 / 60						
Frequency Range (Hz)	45 ~ 65						
Max. Current to Grid (A)	7.9@230V 8.3@220V	9.6@230V 10@220V	12.8@230V 13.4@220V	15.9@230V 16.7@220V	19.1@230V 20@220V	23.9@230V 25@220V	31.9@230V 33.3@220V
Max. Current From Grid (A)	70						
Nominal Current From Grid (A)	7.5@220V 7.2@230V	9.1@220V 8.7@230V	12.1@220V 11.6@230V	15.2@220V 14.5@230V	18.2@220V 17.4@230V	22.7@220V 21.7@230V	30.3@220V 29@230V
Nominal Current to Grid (A)	7.5@220V 7.2@230V	9.1@220V 8.7@230V	12.1@220V 11.6@230V	15.2@220V 14.5@230V	18.2@220V 17.4@230V	22.7@220V 21.7@230V	30.3@220V 29.0@230V
Power Factor	~1 (Adjustable from 0.8 leading ~ 0.8 lagging)						
THDI	<3%						
Back-up Side							
Nominal Output Apparent Power (kVA)	5	6	8	10	12	15	20
Max. Output Apparent Power (kVA)	5.5 (10.0, 10s)	6.6 (12.0, 10s)	8.8 (16.0, 10s)	11.0 (20.0, 10s)	13.2 (24.0, 10s)	16.5 (30.0, 10s)	22.0 (40.0, 10s)
Max. Output Apparent Power with Grid (kVA)	48.3						
Max. Output Current (Bypass)	70						
Nominal Output Voltage (V)	400 / 380, 3L / N / PE						
Nominal Output Frequency (Hz)	50 / 60						
Generator Side							
Nominal Apparent Power (kVA)	20						
Max. Apparent Power (kVA)	20						
Nominal Voltage (V)	400 / 380						
Nominal Frequency (Hz)	50 / 60						
Frequency Range (Hz)	45 ~ 55 / 55 ~ 65						
Max. Current (A)	30.3						
Efficiency							
Max. Efficiency	97.8%	97.8%	97.8%	97.8%	97.8%	97.9%	97.8%
European Efficiency	97.0%	97.0%	97.1%	97.3%	97.3%	97.3%	97.4%
Max. Battery to AC Efficiency	95.5%						
MPPT Efficiency	99.9%						
Protection							
PV String Current Monitoring	Integrated						
PV Insulation Resistance Detection	Integrated						
Residual Current Monitoring	Integrated						
PV Reverse Polarity Protection	Integrated						
Battery Reverse Polarity Protection	Optional	Optional	Optional	Optional	Optional ⁵	Optional ⁵	Optional ⁵
Anti-islanding Protection	Integrated						
AC Overcurrent Protection	Integrated						
AC Short Circuit Protection	Integrated						
AC Overvoltage Protection	Integrated						
DC Switch	Integrated						
DC Surge Protection	Type II						
AC Surge Protection	Type II						
AFCI ⁶	Optional						
Rapid Shutdown	Optional						
Remote Shutdown	Integrated						
General Data							
Operating Temperature Range (°C)	-35 ~ +60						
Relative Humidity	0 ~ 95%						
Max. Operating Altitude (m)	4000						
Cooling Method	Smart Fan Cooling						
User Interface	LCD						
Communication with BMS	CAN						
Communication	WiFi+LAN+Bluetooth, 4G, RS485, CAN						
Communication Protocols	Modbus RTU (RS485), Modbus TCP / IP (Ethernet), Sunspec Modbus RTU						
Weight (kg)	42.2	42.2	42.2	45.3	45.3	49.7	51.2
Dimension (W x H x D mm)	551 x 756 x 258						
Noise Emission (dB)	<45						
Power Self-consumption at Night (kW)	<15						
Ingress Protection Rating	IP66						
Anti-corrosion Class	C4						
Mounting Method	Wall Mounted						

¹: When the input voltage is greater than 980V, the inverter will enter standby mode, and when the voltage returns to below 950V the inverter will return to normal operation.
²: Please refer to the user manual for the MPPT Voltage Range at Nominal Power.
³: For Brazil and Chile, the Max. Power is the same with the Nominal Power.
⁴: For Chile, Max. Apparent Power to Utility Grid is same as Nominal Apparent Power Output to Grid.

⁵: For Brazil, for GW12K-ET-L-G10, GW15K-ET-L-G10 and GW20K-ET-L-G10, the Battery Reverse Polarity Protection is integrated.
⁶: AFCI is integrated in Brazil.
^{*}: Please visit GoodWe website for the latest certificates.
^{*}: All pictures shown are for reference only. Actual appearance may vary.

GoodWe-Single page-20260130-EN-V2.1. Information may be subject to change without notice during product improving.